Options and Accessories



Lighting Package*



Plastic Canopy Top



Custom Van Box



Rear Cargo Cage



Electric Bed Lift



Underhood Storage (Gas Only)



Stake-Side Kit



2-Inch Front Receiver Hitch



Cargo Bed Toolbox



2,500 lb Warn Winch



Pintle Hitch



Nerf Bars



54- or 62-Inch Plow Blade



Swisher Trailmower



Swisher Dump Cart



50-Gallon Sprayer

*Includes horn, turn signals and brakelights



Ingersoll Rand is a world leader in the field of compact vehicles and equipment. Our widely known Bobcat® brand includes an extensive line of powerful, nimble compact construction equipment and attachments, and our state-ofthe-art engineering capabilities and stylish designs are reflected in our world famous Club Car® vehicles.

1.800.ClubCar • +1 706.863.3000

www.clubcar.com www.bobcat.com www.ingersollrand.com

Club Car

CARRYALL 225

UTILITY VEHICLE Intellitach





CARRYALL Intellitach

Like no other utility vehicles on the market, the Carryall 295 IntelliTach™ has brought the utility vehicle world to a whole new level. With its quick-change attachment system, your vehicle is ready to work — no matter what the job may be. Whether you need a set of forks or a bucket, a blade or a broom, this utility vehicle can help get a lot of work done — in a little amount of time. In fact, the Carryall 295 IntelliTach is so multipurpose, it eliminates the need for multiple vehicles helping to keep your operational costs down. Easy-to-use, costeffective and reliable – the Carryall 295 IntelliTach is the



smart utility vehicle.

Standard Color: **Features** 20 hp liquid-cooled Dark Gray Kubota® diesel engine IntelliTrak™: An automatic full-time, All-Wheel-Drive system **Optional Color:** Green Roll Over Protective Structure certified to meet 5 different international Rustproof, non-corrosive, standards box tube 6061 aircraft-grade aluminum frame, chassis and cargo box 15.1 ft³ (0.4 m³) Cargo Box carries 800 lb (362.9 kg) 4-wheel, Double A-Arm hydraulic front suspension disc brakes w/coil-over shocks Mower Forks Push Broom Blade Bucket

Additional Features

Maximum speed of 25 mph (40.2 kph)

w/60"deck

- 1,200 lb (544.3 kg) total vehicle capacity; heavy-duty 1,450 lb (657.7 kg)
- Maximum hp @ 3,600 rpm exceeds SAE J1940 **Performance Standards**
- Able to lift 500 lbs up to 2 feet above ground, no counterweight needed
- 12.1 in (30.7 cm) ground clearance under foot platform to handle rough terrain

(Standard)

25" heavy-duty, all-terrain tire standard; 25" heavyduty, mud tire optional

IntelliTach

Specifications		
		Carryall 295 Diesel IntelliTach
POWER SUPPLY	Engine	Kubota D722,719 cc, 3-cylinder
	Engine – Cooling	Liquid
	Engine – Lubrication & Oil Filter Type	Full-pressure spin-on
	Max Torque	33 ft-lb (44.7 Nm)
	Horsepower	20 (14.9 kw)
	Ignition	Compression
	4WD Engagement	Automatic – IntelliTrak
	Differential – Front	Automatic – IntelliTrak
	Differential – Rear	Auto locking – IntelliTrak
	Electrical System	12-volt, 500 CCA
	Torque Converter	CVT
STEERING/ SUSPENSION	Steering Type	Rack & pinion
	Tilt Steering Wheel	Standard
	Adjustable Driver's Seat	Standard
	Suspension – Front	Independent double A-arms w/coil-over shocks
	Suspension – Rear	Swing arm w/coil-over shocks
	Brakes	4-wheel, hydraulic disc
	Park Brake	Automotive style
FRAME/CHASSIS	Frame/Chassis	Tubular aluminum
	Body – Front	GE Geloy High-impact, scratch-resistant, injection molded color
	Body – Rear	All aluminum cargo bed
	Tires – Front	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
	Tires – Rear	All-terrain, 25 x 10.5-12, 4-ply, (mud tires optional)
	Instrumentation	Electronic fuel gauge/hour meter, seatbelt warning light, low oil warning light, coolant high temp warning light (speedometer optional)
DIMENSIONS	Bed Length x Width x Height	48.8 x 49.8 x 10.9 in (124 x 126.5 x 27.7 cm)
	Overall Bed Height	33 in (83.8 cm)
	Bed Load Capacity	800 lb (362.9 kg)*
	Total Vehicle Capacity	1,200 lb (544.3 kg)**
	Fuel Tank Capacity	6.5 gal (24.6 L)
	Overall Length x Width x Height	148.6 x 60 x 78.6 in (377.4 x 152.4 x 199.6 cm)
	Wheelbase	88.7 in (225.3 cm)
	Ground Clearance – Differential	7.4 in (18.8 cm)
	Tread Centers (Front/Rear)	48.8 in (124 cm) front and rear
	Dry Weight (Less Batteries)	1,475 lb (669.1 kg)
	Maximum Speed	25 mph (40.2 kph)
	Turning Radius	12.1 ft (3.7 m)
	Vehicle Warranty	2-year/2,000-hour, limited
		*1,050 lb (476.3 kg) available **1,450 lb (657.7 kg) available

**1,450 lb (657.7 kg) available