Industrial Hose & Fittings

Foster "Push On" Hose & Fittings



- For shop air, pneumatic tools, petroleum base hydraulic oils, anti-freeze compounds, gasoline, water, lubricating oils and diesel
- No clamps required, just push hose on. Hose grips barb through distortion of braid. Forms leak proof grip with "Pusl fitting. "Push On" hose used with stand barbed fittings requires clamps.

ID	OD	CAT. NO.	PRESSURE	PRESSURE
1/4"	x 9/16"	PO25	300 PSIG	1200 PSIG
3/8"	x 11/16"	PO38	300 PSIG	1200 PSIG
1/2"	x 13/16"	PO50	300 PSIG	1200 PSIG

CONSTRUCTION

· Foster "Push-On" hose is constructed with a synthetic rubber tube, fiber braid reinforcement and a synthetic rubber cover, resistant to abrasion, oil and mildew.

TEMPERATURE RANGE

-40° to +212°F.

	T. D.		
CAT. NO.	CAT. NO.	CAT. NO.	CAT. NO.
PM3			
PM5			
PM7	PM7S	PF36	PHS82
PM9			
PM11			
	PM3 PM5 PM7 PM9	PM3 PM5 PM7 PM7S PM9	PM3 PM5 PM7 PM7S PF36 PM9

SWIVEL

MALE

PM13

PM14

PM16

PM17

PM19

PUSH ON FITTINGS

FEMALE

PF40

PF42

SPLICER

PHS84

PHS85

Foster couplers with "Push-On" hose stems are listed with the various series of sockets and plugs.

PM13S

PM17S

BARBED INSERT FITTINGS **HEX NIPPLES Barbed Inserts FEMALE** MALE FEMALE SPLICERS Require Hose (SOLID) (BALL END) Clamp(s) Brass PIPE THREAD HOSE CAT. NO. CAT. NO. CAT. NO. CAT. NO. CAT. NO. 1/8 NPT x 1/8 M1 1M1M 1/8 NPT x 3/16 M₂ 1/8 NPT x 1/4 МЗ F33 1M2M 1/8 NPT x 5/16 MA 1/8 NPT x 3/8 M₅ 3/16 x 3/16 BHS81 1/4 NPT x 3/16 M6 1/4 NPT x 1/4 M7 F36 SB55 BHS82 2M2M 1/4 NPT x 5/16 M8 1/4 NPT x 3/8 M9 F38 SB57 **2M3M** 1/4 NPT x 1/2 M11 5/16 x 5/16 BHS83 3/8 NPT x 1/4 M12 3/8 NPT x 3/8 M13 F40 SB58 BHS84 змзм 3/8 NPT x 1/2 M14 F41 **3M4M** 1/2 NPT x 3/8 M16 1/2 NPT x 1/2 M17 F42 BHS85 4M4M 1/2 NPT x 3/4 M19 3/4 NPT x 3/4 M22 6M6M

3/8 NPT x 3/8

3/8 NPT x 1/2

1/2 NPT x 3/8

1/2 NPT x 1/2

1/2 NPT x 3/4

