



TWIN HYDRAULIC SERVICE

Series TH

Spring Driven Twin Hose

Series TH - 1/4", 3/8", 1/2" I.D.

The hydraulic series reel incorporates contemporary engineering and manufacturing techniques to give trouble free performance. Used for medium pressure hydraulic applications, Series TH reels are ideal for operating hydraulic cylinders, tools and equipment. They have a high volume dual-body swivel for maximum product delivery (excluding the 80000). Reels are all steel construction and compact for applications with critical space requirements.

Made in USA

	DIMENSIONS					
	TH 5000 OMP		TH 7000 OMP		TH 80000 OMP	
	in / mm		in / mm		in / mm	
A	14 1/2	368	20 1/4	514	25 3/8	645
B	13 1/2	343	19	483	24	610
C	9 3/4	248	7 7/8	200	10	254
D	2 1/2	64	3 7/8	98	6	152
E	6	152	7	177	13	330

C and D dimensions are mounting hole patterns. Four 5/16" (8mm) diameter mounting holes for the 5000 O. Four 1/2" (12.7mm) diameter mounting holes for the 7000 O and 80000.



TH7445 OMP

FEATURES

- ✓ Constant tension or pos-i-latch spool mechanism
- ✓ All steel construction
- ✓ Reels have a durable, abrasion resistant baked-on powder coat finish spring motor
- ✓ Compact design for critical space requirements

Questions? We can help!

Our friendly customer service team is ready to help you with expert assistance. When you call us, you get a live voice and fast, friendly service.

APPLICATIONS

- Cranes
- Construction Equipment
- Hydraulic Tools
- Vehicle Extraction Tools
- Aerial Device
- Hydraulic Cylinders
- Tree Cutters
- Digger Derricks
- Railroad Maintenance Tools

MODELS WITH HOSE			HOSE CAPACITY					MODELS WITHOUT HOSE		
MODEL	WEIGHT	PRESSURE	I.D.	O.D.	(M)NPTF OUTLET	(F)NPTF INLET	LENGTH	MODEL	WEIGHT	PRESSURE
	lbs / kg	psi / bar							in / mm	in / mm
MEDIUM PRESSURE HYDRAULIC HOSE REELS - Maximum Temperature 210° F (99° C)										
TH5425 OMP	34 15	2000 138	1/4 6	.500 13	1/4	1/4	25 8	TH5400 OMP	24 10	3000 207
TH7445 OMP	67 30	2000 138	1/4 6	.500 13	1/4	1/4	45 15	TH7400 OMP	47 22	3000 207
THA7630 OMP	60 27	2000 138	3/8 10	.640 16	3/8	3/8	30 9	THA7600 OMP CA	47 22	3000 207
MEDIUM PRESSURE HOSE REELS - Maximum Temperature 210° F (99° C)										
TH86050 OMP	99 45	2000 138	3/8 10	.640 16	3/8	3/8	50 15	TH86000 OMP	87 39	3000 207
TH88050 OMP	104 47	2000 138	1/2 13	.910 23	1/2	1/2	50 15	TH88000 OMP CA	87 39	3000 207

Adjustable hose bumpers listed on page 51. See page 49 for optional accessories, mounting brackets and bases.

North America: **800-444-3134** Asia: **+63 (45) 625-6624**
 Europe: **+44 (0) 1536 406999** Latin America: **260-489-1685**

www.reelcraft.com



Wind Things Up With Reelcraft™