



# Used and New Tampers

### KEY FEATURES

■ **Industry-leading impact forces:** To achieve desired compaction levels while using maximum lift thickness.

■ **4-cycle Honda engine:** Eliminates need to mix gas and oil. More efficient operation and fuel economy.

■ **Self-balanced design:** Greater maneuverability and maximum control around jobsite obstacles.

■ **4-point isolation and vibration-reducing grip:** Minimizes operator fatigue and prolongs the life of rammer components.

## IR MODEL RX-264H

### DIMENSIONS

Overall Length in (mm)	26.6 (675)
Overall Width in (mm)	15.2 (385)
Overall Height in (mm)	43.3 (1100)
Foot Size (w x l) in (mm)	9 x 13 (230 x 330)
Operating Weight lb (kg)	127 (58)

### PERFORMANCE

Impact Force lb (kN)	2,600 (11.2)
Blows Per Minute	600-750
Travel Speed fpm (mpm)	39-46 (12-14)
Area Capacity Per Hr. sq ft (sq m)	2,100 (195)
Recommended Compaction Depth in (mm)	18 (460)

### ENGINE

Type	Honda, 4-cycle
Model	GX100KRA2
Horsepower hp (kW)	3.0 (2.2)
Engine Speed rpm	4,000
Fuel Tank Capacity qt (L)	2.6 (2.5)

### FOOT OPTIONS

Foot Size (w x l) in (mm)	6 x 13 (152 x 330)
Foot Size (w x l) in (mm)	8 x 13 (200 x 330)
Foot Size (w x l) in (mm)	9 x 13 (230 x 330)

Specifications are subject to change without notice.



### Powerful Performance

Each rammer comes equipped with a rugged and reliable, 4-cycle Honda engine with recoil start engineered to provide years of dependable operation. Oil-splash lubrication reduces the need for daily greasing while ensuring continuous protection of all internal parts. Engine speed remains constant through ratchet-type throttle control. The engine cover protects the operator and machine, yet can be easily removed to allow access to all service components.

EQUIPMENT	DESCRIPTION	AVAILABLE	PRICE
NEW	NEW UNITS	IN STOCK, BALTIMORE	\$ 2,550
2006 USED, UNDER 15HRS	WORKS GREAT	1 AVAILABLE IN Baltimore	\$ 1,000