

## Two Stage Gasoline Drive

| Part Number | HP    | Model      | Engine | Electric and Recoil Start | cfm displ. | cfm 100 psi | Tank gal. | Ship Wt* lbs. | L x W x H inches |
|-------------|-------|------------|--------|---------------------------|------------|-------------|-----------|---------------|------------------|
| 8090250631  | 9     | RCP-930G   | Robin  | Standard                  | 19.1       | 16.0        | 30H       | 328           | 45 x 19 x 38     |
| 8090250606  | 10    | RCP-1030G  | Intek  | Standard                  | 19.1       | 16.0        | 30H       | 328           | 45 x 19 x 38     |
| 8090250607  | 11    | RCP-1130G  | Honda  | Standard                  | 22.4       | 18.5        | 30H       | 358           | 45 x 19 x 45     |
| 8090250823  | 12.75 | RCP-1230GK | Kohler | Standard                  | 22.4       | 18.5        | 30H       | 369           | 45 x 19 x 45     |
| 8090250608  | 12.75 | RCP-1230G  | Kohler | Standard                  | 32.5       | 25.3        | 30H       | 369           | 45 x 19 x 45     |
| 8090250609  | 13    | RCP-1330G  | Honda  | Standard                  | 32.5       | 25.3        | 30H       | 378           | 45 x 19 x 45     |

### STANDARD FEATURES

12 Volt Electric Start and Recoil Start  
 12 Alternator (3G3HH / HHL. Optional 3G3HK / HKL)  
 Start Key / Panel  
 Oil Monitor  
 Engine Slowdown (Pilot Valve)

Fully Enclosed Belt Guard  
 EZ Pull Tank Drain  
 ASME Tank and Safety Valves  
 3/4" Tank Discharge Valve

### OPTIONAL

Engine Oil Drain  
 12 Alternator 3G3HK or 3G3HKL

